

Listing of Claims:

1. (previously presented) A filter element, comprising:
 - a ring of filtration media circumscribing a central axis and defining a central cavity, the filtration media ring having a first end and a second end;
 - a first, circular end cap having an inner surface sealingly bonded to the first end of the media ring, the first end cap including an annular body portion defining a central opening into the central cavity of the media, a sealing device bounding the central opening, a vent orifice in the annular body into the central cavity at a predetermined location, radially outward from the sealing device, and an orientation device permanently fixed to and integral with the first end cap and projecting radially outward therefrom; and
 - a second, circular end cap sealingly bonded to the second end of the media ring, a retaining device fixed to and integral with the second end cap and projecting outwardly therefrom.
2. (previously presented) The filter element as in claim 1, wherein the sealing device comprises a flexible lip seal bounding the central opening of the first end cap.
3. (previously presented) The filter element as in claim 2, wherein the flexible lip seal is unitary with the first end cap.
4. (original) The filter element as in claim 1, wherein the retaining device is unitary with the second end cap.

1 5. (original) The filter element as in claim 1, wherein the first end cap includes a
2 sleeve outwardly bounding the peripheral edge of the first end cap, and extending a short
3 distance from the first end cap toward the second end cap, the orientation device being
4 unitary with the sleeve of the first end cap and projecting radially outward therefrom.

1 6. (previously presented) The filter element as in claim 1, wherein the orientation
2 device is unitary with the first end cap.

1 7. (currently amended) The filter element as in claim 1, wherein the retaining
2 ~~devices comprise~~ device comprises a plurality of individual elements, fixed to and
3 integral with the second end cap and projecting radially outward therefrom.

1 8. (cancelled) The filter element as in claim 1, wherein the retaining device projects
2 axially outward from the second end cap.

1 9. (original) The filter element as in claim 1, wherein the retaining device projects
2 radially outward from the second end cap.

1 10. (original) The filter element as in claim 1, wherein the second end cap includes a
2 sleeve outwardly bounding the peripheral edge of the second end cap, and extending a
3 short distance from the second end cap toward the first end cap, the retaining device
4 being unitary with the sleeve of the second end cap and projecting radially outward
5 therefrom.

11. (previously presented) A filter assembly comprising a housing having a threaded open end, a closed end, and a central axis, a first port to direct fluid into the housing and a second port to direct fluid from the housing, the housing including orientation means integral with an internal surface of the housing and projecting outwardly therefrom; a cup-shaped cover with threads adapted to be screwed down onto the threaded open end of the housing, the cover including retaining means internally of the cover; and a filter element removably disposed within the housing, the filter element including a ring of filtration media circumscribing a central axis and defining a central cavity, the filtration media ring having a first end and a second end; a first, circular end cap at the first end of the media ring, and an annular body portion defining a central opening for receiving a cylindrical component, and an annular seal bounding the central opening of the first end cap for providing a fluid seal with the cylindrical component, a vent orifice in the first end cap into the central cavity of the filter element, disposed radially outward from the seal, and a cooperating orientation means permanently fixed to and integral with the first end cap and projecting outwardly therefrom, the orientation means of the first end cap having a configuration such that the orientation means on the first end cap cooperates with the orientation means in the housing when the element is fully received therein to rotationally orient the filter element with respect to the housing such that the orifice in the first end cap is in a predetermined rotational position relative to the housing; and

a second, circular end cap at the second end of the media ring, the second end cap including retaining means, the retaining means of the second end cap interengaging with the retaining means of the cover to temporarily couple the end cap to the cover when the cover is initially screwed down onto the housing, wherein when the cover is initially screwed down onto the housing, the filter element rotates in conjunction with the cover until the cover is screwed down a predetermined amount, after which the orientation means of the first end cap engages the orientation means of the housing, to rotationally lock the filter element with respect to the housing, the interengagement between the cover

and element being such that when the orientation means of the housing and first end cap engage, the cover can thereafter rotate with respect to the filter element as the cover is fully screwed down onto the housing, and when the cover is removed to replace a spent element, the orientation means remaining with the element as the element is removed from the housing.

12. (previously presented) A filter assembly comprising a housing having a threaded open end, a closed end, and a central axis, a first port to direct fluid into the housing and a second port to direct fluid from the housing, the housing including an orientation device integral with an internal surface of the housing and projecting radially inward therefrom; a cup-shaped cover with threads adapted to be screwed down onto the threaded open end of the housing, the cover including a retaining device internally of the cover and projecting radially outwardly therefrom; and a filter element removably disposed within the housing, the filter element including a ring of filtration media circumscribing a central axis and defining a central cavity, the filtration media ring having a first end and a second end; a first, circular end cap at the first end of the media ring, having an annular body portion defining a central opening for receiving a cylindrical component, and an annular seal bounding the central opening of the first end cap for providing a fluid seal with the cylindrical component, a vent orifice in the first end cap into the central cavity of the filter element, disposed radially outward from the seal, and a cooperating orientation device permanently fixed to and integral with the first end cap and projecting radially outwardly therefrom, the orientation device of the first end cap having a configuration such that the orientation device on the first end cap cooperates with the orientation device in the housing when the element is fully received therein to rotationally orient the filter element with respect to the housing such that the orifice in the first end cap is in a predetermined rotational position relative to the housing; and

a second, circular end cap at the second end of the media ring, a retaining device integral with the second end cap and projecting outwardly therefrom, the retaining device

23 of the second end cap having a configuration such that the retaining device of the second
24 end cap interengages with the retaining device on the cover to temporarily couple the end
25 cap to the cover when the cover is initially screwed down onto the housing, wherein
26 when the cover is initially screwed down onto the housing, the filter element rotates in
27 conjunction with the cover until the cover is screwed down a predetermined amount, after
28 which the orientation device on the first end cap engages the orientation device on the
29 housing, to rotationally lock the filter element with respect to the housing, the
30 interengagement between the cover and element being such that when the orientation
31 device on the housing and first end cap engage, the cover can thereafter rotate with
32 respect to the filter element as the cover is fully screwed down onto the housing.

1 13. (currently amended) The filter assembly as in claim 12, wherein the retaining
2 device on the ~~cover~~ second end cap comprises a rib, ridge or tab, and the retaining device
3 on the ~~second end cap cover~~ comprises a pair of closely-spaced ribs, ridges or tabs for
4 each retaining device on the ~~cover~~ second end cap.

1 14. (original) The filter assembly as in claim 12, wherein the orientation device on the
2 first end cap comprises a rib, ridge or tab and the orientation device on the housing
3 comprises a rib, ridge or tab.

1 15. (previously presented) The filter element as in claim 1, wherein the vent orifice is
2 disposed radially intermediate the sealing device and the media ring.

1 16. (previously presented) The filter element as in claim 1, further including an
2 annular locating sleeve projecting outwardly from the annular body portion, radially
3 outwardly spaced from the sealing device.

1 17. (previously presented) The filter element as in claim 16, wherein the locating
2 sleeve is radially outwardly disposed from the vent orifice, and includes a notch located
3 in radial alignment with the vent orifice.

1 18. (previously presented) The filter assembly as in claim 11, further including an
2 annular locating sleeve projecting outwardly from the annular body portion, disposed
3 radially outward from the central opening, and the vent orifice is disposed radially
4 between the seal and the locating sleeve, and the housing includes a corresponding
5 annular channel located so as to receive the locating sleeve when the filter element is
6 located in the housing, so as to locate and support the element in the housing..

1 19. (currently amended) The filter ~~element~~ assembly as in claim 18, wherein the
2 locating sleeve includes a notch located in radial alignment with the vent orifice.

1 20. (previously presented) The filter assembly as in claim 12, further including an
2 annular locating sleeve projecting outwardly from the annular body portion, disposed
3 radially outward from the central opening, and the vent orifice is disposed radially
4 between the seal and the locating sleeve, and the housing includes a corresponding
5 annular channel located so as to receive the locating sleeve when the filter element is
6 located in the housing, so as to locate and support the element in the housing..

1 21. (currently amended) The filter ~~element~~ assembly as in claim 20, wherein the
2 locating sleeve includes a notch located in radial alignment with the vent orifice.

1 22. (previously presented) A filter element, comprising:
2 a ring of filtration media circumscribing a central axis and defining a central
3 cavity, the filtration media ring having a first end and a second end;

4 a first, circular end cap having an inner surface sealingly bonded to the first end of the
5 media ring, the first end cap including an annular body portion defining a central opening
6 into the central cavity of the media, sealing means bounding the central opening for
7 sealing against a circular collar, an annular locating sleeve radially outwardly spaced
8 from the central opening and projecting outwardly from the annular body portion, a vent
9 orifice in the annular body into the central cavity at a predetermined circumferential
10 location, radially disposed between the sealing means and locating sleeve, and orientation
11 means permanently fixed to and integral with the first end cap and projecting radially
12 outward therefrom for rotationally orienting the filter element within a cylindrical
13 housing, the orientation means remaining with the element when the filter element is
14 removed from the housing; and

15 a second, circular end cap sealingly bonded to the second end of the media ring,
16 retaining means fixed to and integral with the second end cap and projecting outwardly
17 therefrom for temporarily retaining the element within a cover.

1 23. (new) The filter element as in claim 22, wherein the sleeve includes a notch
2 located in radial alignment with the vent orifice.

1 24. (new) The filter element as in claim 16, wherein the locating sleeve is
2 discontinuous, and includes a notch.

1 25. (new) The filter assembly as in claim 18, wherein the locating sleeve is
2 discontinuous, and includes a notch.

1 26. (new) The filter assembly as in claim 20, wherein the locating sleeve is
2 discontinuous, and includes a notch.

Application Serial No. 10/669,118
Response to Office Action dated August 16, 2007
Amendment dated September 23, 2007

27. (new) The filter element as in claim 22, wherein the locating sleeve is discontinuous, and includes a notch.